




7系列---底板型---活动式/固定式

- 每个轮最大承载1600公斤
- 底板厚8mm
- 安装孔径14.2mm



Swivel Cross Section



轮径 (mm)	轮宽 (mm)	承载 (kg)	单轮	轴承	型号		重量 (kg)	安装高度 (mm)	转动半径 (mm)
					活动	固定			
150	64	726	酚醛	滚柱	7-6609-369	7-6608-369	8.17	203	146
		1135	生铁铸造		7-6609-169	7-6608-169	10.89		
			V型槽		7-6609-769	7-6608-769	10.89		
			锻压钢		7-6609-269	7-6608-269	10.44		
	76	306	粘合包橡胶		7-6609-679	7-6608-679	8.97		
		908	粘合包聚氨酯		7-6609-979	7-6608-979	8.7		
200	64	908	酚醛	滚柱	7-8609-369	7-8608-369	9.53	267	171
		76	381		粘合包橡胶	7-8609-679	7-8608-679		
	1135		粘合包聚氨酯		7-8609-979	7-8608-979	10.7		
			生铁铸造		7-8609-179	7-8608-179	14.99		
			V型槽		7-8609-779	7-8608-779	12.48		
	1589	锻压钢	7-8609-279		7-8608-279	16.48			
250	64	545	高科技聚氨酯	滚柱	7-10609-959	7-10608-959	11.8	318	190
		454	粘合包橡胶		7-10609-679	7-10608-679	13.8		
		1317	酚醛		7-10609-379	7-10608-379	13.16		
	76	1362	粘合包聚氨酯		7-10609-979	7-10608-979	11.58		
		生铁铸造	7-10609-179		7-10608-179	18.61			
		1600	锻压钢		7-10609-279	7-10608-279	17.25		
300	76	518	粘合包橡胶	滚柱	7-12609-679	7-12608-679	15.75	394	235
		1362	生铁铸造		7-12609-179	7-12608-179	19.86		
		1600	酚醛		7-12609-379	7-12608-379	15.08		
			粘合包聚氨酯		7-12609-979	7-12608-979	13.6		